

AR40 - Paint stirrer

IMPORTANT FOR OUR 1-LITER BINS



YSHIELD® AR40

Characteristics

Paint stirrer to mix up our shielding paints. Our **1-liter paint containers have an opening of 40 mm diameter**. None of the usual paint stirrers will fit in this opening. That's why we have developed a stirrer by ourselves. Our paint stirrer is mixing up shielding paints quickly and consistently, even in slim and high paint containers.

DKL90 - Dispersion glue

FOR OUR NETTINGS AND FLEECES



YSHIELD® DKL90

Characteristics

Special coordinated dispersion glue for binding our sheet materials to walls, ceilings, floors, doors, etc.. High quality class water-resistant special glue based on acrylics, breathable, low-emission and solvent-free. **Electrically conductive**, that the materials don't get isolated for grounding.

Processing

The application is identical to a wallpaper glue! Avoid bucklings and wrinkles in the materials! The wall surface and the backside of the material is primed with a painter's roller. The material is inserted

wet-on-wet and fixed by hand (with disposable gloves) or with a pressure roller. Work quickly and strip by strip so that the glue won't get dry.

Technical data

- **Specially for the following materials:** HNG80, HNG100, NCV95
- **Delivery sizes:** 5 liter
- **Coverage:** 17.5 m² - 25 m², depending on the underground
- **Ingredients:** Acrylic binder, water, carbon black, additives, preservative (MIT, BIT)
- **Color:** Black
- **Surface conductivity:** 400 ohm (square resistance R_□)